

## UDOT Minimum Sampling and Testing Requirements

### *Specification - Material: 02786 Open Graded Surface Course*

**Assurance:** Asphalt Binder Content and Sieve Analysis

**Reference:** AASHTO T 308 and AASHTO T 30

**Lot Size:** Production Day

**Frequency per Lot:** Four samples per production day is standard, for exceptions see Section 02786 "Acceptance."

**Point of Acceptance:** Hot Plant

**Sampling Reference:** MOI 8-984

**Report/Form:** Materials Database

---

**Assurance:** Thickness

**Reference:** Verify with a depth probe

**Lot Size:**

**Frequency per Lot:**

**Point of Acceptance:**

**Sampling Reference:**

**Report/Form:**

---

**Assurance:** Smoothness

**Reference:** Standard Specification 01452

**Lot Size:**

**Frequency per Lot:**

**Point of Acceptance:**

**Sampling Reference:**

**Report/Form:**

---

**Assurance:** Visual Acceptance of very small quantities of materials

**Reference:** Acceptance is limited to material being furnished from sources found satisfactory under normal sampling and testing procedures.

**Lot Size:** Not to exceed 100 tons per day or 1000 tons per project

**Frequency per Lot:** One report for each day material is accepted

**Point of Acceptance:** Grade

**Sampling Reference:**

**Report/Form:**

---